

AMENDMENTS TO THE CLAIMS

WE CLAIM (clean copy)

5 1. (canceled)

2. (canceled)

3. (canceled)

4. (canceled)

5. (canceled)

10 6. (canceled)

7. (canceled)

8. (canceled)

9. (currently amended) A method of performing a k-stage FFT (fast Fourier transform) computation of N data points wherein k and N are integers, the method comprising:

15 for each one of a plurality of stage groupings of at least one stage of k stages of the k-stage FFT computation wherein the plurality of stage groupings of at least one stage collectively comprise the k stages, performing a respective plurality of operations on the N data points, each one of the respective plurality of operations comprising:

20 performing an import of a respective plurality of sets of data points of the N data points from an external memory into an internal memory;

performing a FFT computation upon each one of the respective plurality of sets of data points of the N data points in the internal memory; and

25 performing an export of the respective plurality of sets of data points of the N data points from the internal memory into the external memory to update the respective plurality of sets of data points of the N data points in the external memory, wherein the stage groupings of at least one stage comprise Q stage groupings each

comprising S stages, said Q and said S being integers with $Q \geq 1$, $S \geq 1$ and $k \geq QS$, and wherein N substantially satisfies $N = 2^k$, the method further comprising:

grouping, within a stage grouping, I, of the Q stage groupings wherein I is an integer satisfying $0 \leq I \leq Q-1$, the N data points into 2^{IS} blocks of data of $N/2^{IS}$ respective data points;

grouping, within each one of the 2^{IS} blocks of data, the $N/2^{IS}$ respective data points into 2^S sub-blocks of data of $N/2^{IS+S}$ respective data points;

grouping, within each one of the 2^S sub-blocks of data, the $N/2^{IS+S}$ respective data points into M_1 sub-sub-blocks of data of $N/(2^{IS+S} M_1)$ respective data points wherein M_1 is an integer;

taking, within each one of the 2^{IS} blocks of data, a respective sub-sub-block of data of the M_1 sub-sub-blocks of data from each one of the 2^S sub-blocks of data to form a set of 2^S sub-sub-blocks of data of $N/(2^{IS} M_1)$ data points a total of M_1 times to produce M_1 sets of 2^S sub-sub-blocks of data of $N/(2^{IS} M_1)$ data points; and

taking, within each one of the M_1 sets of 2^S sub-sub-blocks of data, a respective data point from each one of the 2^S sub-blocks of data to form a set of 2^S data points a total of $N/(2^{IS+S} M_1)$ times to produce $N/(2^{IS+S} M_1)$ sets of 2^S data points.

10. (original) A method of performing a k-stage FFT computation according to claim 9 wherein, for the stage grouping, I, of the of the Q stage groupings of the plurality of stage groupings, the performing a respective plurality of operations on the N data points comprises performing M_1 of the plurality of operations for each one of the 2^{IS} blocks of data within the stage grouping, I, each one of the M_1 of the plurality operations comprising:

performing an import of respective $N/(2^{IS+S} M_1)$ sets of 2^S data points from the external memory into the internal memory;

performing an S-stage FFT computation of the k-stage FFT computation upon each set of 2^S data points of the respective $N/(2^{IS+S} M_1)$ sets of 2^S data points in the internal memory; and

performing an export of the respective $N/(2^{IS+S}M_1)$ sets of 2^S data points

from the internal memory into the external memory to update the respective $N/(2^{IS+S}M_1)$ sets of 2^S data points in the external memory.

11. (original) A method of performing a k-stage FFT computation according to claim
5 10 wherein M_1 substantially satisfies $M_1 = N/(2^{IS}M_1)$ wherein M_1 corresponds to the number of data points the internal memory can hold.
12. (original) A method of performing a k-stage FFT computation according to claim
10 wherein M_1 substantially satisfies $M_1 = N/(2^{IS-1}M_1)$ wherein M_1 corresponds to the number of data points a buffer in the internal memory can hold.
- 10 13. (original) A method of performing a k-stage FFT computation according to claim
10 wherein the performing an S-stage FFT computation of the k-stage FFT computation upon each set of 2^S data points of the respective $N/(2^{IS+S}M_1)$ sets of 2^S data points results in $N/(2^{IS+S}M_1)$ S-stage FFT computations, the $N/(2^{IS+S}M_1)$ S-stage FFT computations comprising performing one stage of S stages for each one of the
15 $N/(2^{IS+S}M_1)$ S-stage FFT computations and iterating through the S stages.
14. (original) A method of performing a k-stage FFT computation according to claim
10 wherein the performing an S-stage FFT computation of the k-stage FFT computation upon each set of 2^S data points of the respective $N/(2^{IS+S}M_1)$ sets of 2^S data points results in $N/(2^{IS+S}M_1)$ S-stage FFT computations, the $N/(2^{IS+S}M_1)$ S-stage
20 FFT computations comprising performing computations for S stages of an S-stage FFT computation of one of the $N/(2^{IS+S}M_1)$ S-stage FFT computations before another S-stage FFT computation is performed on another of one of the $N/(2^{IS+S}M_1)$ S-stage FFT computations.
15. (canceled)
- 25 16. (canceled)
17. (canceled)
18. (canceled)
19. (canceled)

20. (canceled)

21. (canceled)

22. (canceled)

23. (canceled)

5 24. (canceled)

25. (canceled)

26. (currently amended) A processor comprising:

an internal memory adapted to store data;

10 a DMA (direct memory access) unit adapted to import data into the internal memory and to export data from the internal memory; and

a central processor unit (CPU) adapted to perform, for each one of a plurality of stage groupings of at least one stage of k stages of the k-stage FFT computation wherein the plurality of stage groupings of at least one stage collectively comprise the k stages, a respective plurality of operations on the N data points, for each
15 one of the respective plurality of operations the CPU is adapted to:

provide instructions to the DMA unit for performing an import of a respective plurality of sets of data points, of N data points, into the internal memory;

perform a FFT computation upon each one of the respective plurality of sets of data points, of the N data points, in the internal memory; and

20 provide instructions to the DMA unit for performing an export of the respective plurality of sets of data points, of the N data points, from the internal memory to update the respective plurality of sets of data points of the N data points, wherein the CPU is adapted to:

group, within a stage grouping, I, of the Q stage groupings wherein I is
25 an integer satisfying $0 \leq I \leq Q-1$, the N data points into 2^{IS} blocks of data of $N/2^{IS}$ respective data points;

group, within each one of the 2^{IS} blocks of data, the $N/2^{IS}$ respective data points into 2^S sub-blocks of data of $N/2^{IS+S}$ respective data points;

group, within each one of the 2^S sub-blocks of data, the $N/2^{IS+S}$ respective data points into M_1 sub-sub-blocks of data of $N/(2^{IS+S} M_1)$ respective data points wherein M_1 is an integer;

take, within each one of the 2^{IS} blocks of data, a respective sub-sub-block of data of the M_1 sub-sub-blocks of data from each one of the 2^S sub-blocks of data to form a set of 2^S sub-sub-blocks of data of $N/(2^{IS} M_1)$ data points a total of M_1 times to produce M_1 sets of 2^S sub-sub-blocks of data of $N/(2^{IS} M_1)$ data points; and

take, within each one of the M_1 sets of 2^S sub-sub-blocks of data, a respective data point from each one of the 2^S sub-blocks of data to form a set of 2^S data points a total of $N/(2^{IS+S} M_1)$ times to produce $N/(2^{IS+S} M_1)$ sets of 2^S data points.

27. (original) A processor according to claim 26 wherein, for the stage grouping, I, of the of the Q stage groupings of the plurality of stage groupings, the CPU is adapted to perform M_1 of the plurality operations for each one of the 2^{IS} blocks of data within the stage grouping, I, and for each one of the M_1 of the plurality operations the CPU is adapted to:

provide instructions to the DMA unit for performing an import of respective $N/(2^{IS+S} M_1)$ sets of 2^S data points into the internal memory;

performing an S-stage FFT computation of the k-stage FFT computation upon each set of 2^S data points of the respective $N/(2^{IS+S} M_1)$ sets of 2^S data points in the internal memory; and

provide instructions to the DMA unit for performing an export of the respective $N/(2^{IS+S} M_1)$ sets of 2^S data points from the internal memory to update the respective $N/(2^{IS+S} M_1)$ sets of 2^S data points.

28. (original) A processor according to claim 27 wherein the internal memory comprises a buffer adapted to store the plurality of sets of data points, wherein the buffer has a capacity to hold M_1 data points and M_1 substantially satisfies $M_1 = N/(2^{IS} M_1)$ wherein M_1 in an integer.

29. (original) A processor according to claim 27 wherein the internal memory comprises a double buffer adapted to store the plurality of sets of data points, wherein the double buffer comprises two buffers each capable of storing $M_1/2$ data points and wherein said M_1 substantially satisfies $M_1 = N/(2^{IS-1}M_1)$, M_1 being an integer.

5 30. (original) A processor according to claim 29 wherein while the CPU performs the S-stage FFT computation of the k-stage FFT computation upon each set of 2^S data points of the respective $N/(2^{IS+S}M_1)$ sets of 2^S data points, the respective $N/(2^{IS+S}M_1)$ sets of 2^S data points being stored in one of the two buffers, the CPU is adapted to provide instructions to the DMA unit to import, into another one of the two buffers,
10 respective $N/(2^{IS+S}M_1)$ sets of 2^S data points of a next one of the each one of the M_1 of the plurality operations.

31. (original) A processor according to claim 29 wherein while the CPU performs the S-stage FFT computation of the k-stage FFT computation upon each set of 2^S data points of the respective $N/(2^{IS+S}M_1)$ sets of 2^S data points, the respective $N/(2^{IS+S}M_1)$
15 sets of 2^S data points being stored in one of the two buffers, the CPU is adapted to provide instructions to the DMA unit to export, from another one of the two buffers, respective $N/(2^{IS+S}M_1)$ sets of 2^S data points from previous one of the each one of the M_1 of the plurality operations.

32. (original) A processor according to claim 27 wherein the performing an S-stage
20 FFT computation of the k-stage FFT computation upon each set of 2^S data points of the respective $N/(2^{IS+S}M_1)$ sets of 2^S data points results in $N/(2^{IS+S}M_1)$ S-stage FFT computations, the CPU being further adapted to evaluate the $N/(2^{IS+S}M_1)$ S-stage FFT computations at one stage of S stages for each one of the $N/(2^{IS+S}M_1)$ S-stage FFT computations and iterate through the S stages.

25 33. (original) A processor according to claim 27 wherein the internal memory comprises a high-speed cache.

34. (original) A processor according to claim 33 wherein the performing an S-stage
FFT computation of the k-stage FFT computation upon each set of 2^S data points of the respective $N/(2^{IS+S}M_1)$ sets of 2^S data points results in $N/(2^{IS+S}M_1)$ S-stage FFT
30 computations, the CPU being further adapted to perform computations for S stages of an S-stage FFT computation of one of the $N/(2^{IS+S}M_1)$ S-stage FFT computations

before performing another S-stage FFT computation of another one of the $N/(2^{IS+S} M_1)$
S-stage FFT computations.

35. (original) A processor according to claim 28 wherein the stage groupings of at
least one stage comprise a stage grouping of D stage wherein D is an integer, said k
5 substantially satisfying $k=QS+D$ and said D substantially satisfying $D \leq \log_2(M_1)$.

36. (original) A processor according to claim 29 wherein the stage groupings of at
least one stage comprise a stage grouping of D stage wherein D is an integer, said k
substantially satisfying $k=QS+D$ and said D substantially satisfying $D \leq \log_2(M_1/2)$.

37. (canceled)

10 38. (canceled)

39. (canceled)

40. (canceled)

41. (currently amended) An article of manufacture comprising:

a computer usable medium having computer readable program code
15 means embodied therein for performing a k-stage FFT computation of N data points
wherein k and N are integers, the computer readable code means in said article of
manufacture comprising:

computer readable code FFT means for performing, for each one of a
plurality of stage groupings of at least one stage of k stages of the k-stage FFT
20 computation wherein the plurality of stage groupings of at least one stage collectively
comprise the k stages, a respective plurality of operations on the N data points, for each
one of the respective plurality of operations the computer readable code FFT means
comprising:

computer readable code means for providing instructions for performing
25 an import of a respective plurality of sets of data points of the N data points from an
external memory into an internal memory;

computer readable code means for performing a FFT computation upon
each one of the respective plurality of sets of data points of the N data points in the
internal memory; and

computer readable code means for providing instructions for performing
5 an export of the respective plurality of sets of data points of the N data points from the
internal memory into the external memory to update the respective plurality of sets of
data points of the N data points in the external memory, wherein the stage groupings of
at least one stage comprise a stage grouping of D stage and Q stage groupings of S
stages wherein D, Q and S are integers and wherein said k substantially satisfies
10 $k=QS+D$ and $k = \log_2(N)$, the article of manufacture comprising further computer
readable code means for:

grouping, within a stage grouping, I, of the Q stage groupings wherein I
is an integer satisfying $0 \leq I \leq Q-1$, the N data points into 2^{IS} blocks of data of $N/2^{IS}$
respective data points;

15 grouping, within each one of the 2^{IS} blocks of data, the $N/2^{IS}$ respective
data points into 2^S sub-blocks of data of $N/2^{IS+S}$ respective data points;

grouping, within each one of the 2^S sub-blocks of data, the $N/2^{IS+S}$
respective data points into M_1 sub-sub-blocks of data of $N/(2^{IS+S} M_1)$ respective data
points wherein M_1 is an integer;

20 taking, within each one of the 2^{IS} blocks of data, a respective sub-sub-
block of data of the M_1 sub-sub-blocks of data from each one of the 2^S sub-blocks of
data to form a set of 2^S sub-sub-blocks of data of $N/(2^{IS} M_1)$ data points a total of M_1
times to produce M_1 sets of 2^S sub-sub-blocks of data of $N/(2^{IS} M_1)$ data points; and

taking, within each one of the M_1 sets of 2^S sub-sub-blocks of data, a
25 respective data point from each one of the 2^S sub-blocks of data to form a set of 2^S data
points a total of $N/(2^{IS+S} M_1)$ times to produce $N/(2^{IS+S} M_1)$ sets of 2^S data points.

42. (original) An article of manufacture according to claim 41 wherein, for the stage
grouping, I, of the of the Q stage groupings of the plurality of stage groupings, the
computer readable code FFT means is further adapted to perform M_1 of the plurality
30 operations for each one of the 2^{IS} blocks of data within the stage grouping, I, and for

each one of the M_1 of the plurality operations the computer readable code FFT means further comprising:

computer readable code means for providing instructions for performing an import of respective $N/(2^{IS+S}M_1)$ sets of 2^S data points from the external memory
5 into the internal memory;

computer readable code means for performing an S-stage FFT computation of the k-stage FFT computation upon each set of 2^S data points of the respective $N/(2^{IS+S}M_1)$ sets of 2^S data points in the internal memory; and

computer readable code means for providing instructions for performing
10 an export of the respective $N/(2^{IS+S}M_1)$ sets of 2^S data points from the internal memory into the external memory to update the respective $N/(2^{IS+S}M_1)$ sets of 2^S data points in the external memory.

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.